



### DRB862

#### All steel radial tire >>>

- Suitable for all wheels on mixed or even poor road condition
- Excellent in tearing resistance
- Outstanding performance in heat dispersion and comprehensive performance



Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
6.50R16LT	10	5.50F	5.00F		180	750	975	850	560	560	107/102 M
6.50R16LT	12	5.50F	5.00F		180	750	1060	925	670	670	110/105 M
7.00R16LT	12	5.50F	6.00G		195	775	1215	1060	770	770	115/110 M
7.00R16LT	14	5.50F	6.00G		195	775	1320	1118	670	670	118/114 L
7.50R16LT	14	6.00G	5.50F	6.50H	215	805	1500	1320	770	770	122/118 L
8.25R16LT	16	6.50H	6.00G	6.5	235	855	1800	1600	770	770	128/124 L
7.50R20	14	6.0	6.5	6.50T	215	935	1900	1800	830	830	130/128 L
8.25R20	16	6.5	6.50T	7.0 7.00T	236	974	2430	2300	930	930	139/137 K
9.00R20	16	7.0	7.00T	7.5	259	1019	2800	2650	900	900	144/142 K
10.00R20	18	7.5	7.50V	8.0	278	1054	3250	3000	930	930	149/146 K
11.00R20	18	8.0	8.00V	8.5	293	1085	3550	3250	930	930	152/149 K
12.00R20	18	8.5	8.50V	9.0	315	1125	3750	3450	830	830	154/151 K
12.00R20	20	8.5	8.50V	9.0	315	1125	4000	3650	900	900	156/153 K
12.00R24	18	8.5	8.50V	9.0	315	1226	4250	3875	830	830	158/155 K
12.00R24	20	8.5	8.50V	9.0	315	1226	4500	4125	900	900	160/157 K
11R22.5	16	8.25	7.50		279	1054	3000	2725	830	830	146/143 L
12R22.5	18	9.00	8.25		300	1085	3550	3250	930	930	152/149 L
13R22.5	18	9.75	9.00		315	1120	3750	3450	830	830	154/151 K
315/80R22.5	18	9.00	9.75		312	1076	3750	3450	830	830	154/151 L
315/80R22.5	20	9.00	9.75		312	1076	4125	3750	900	900	157/154 L

### DRB868

#### All steel radial tire >>>

- Suitable for all wheels on complicated road condition
- Strong traction and ground grip performance
- Good performance of anti-irregular wear



Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
12.00R24	18	8.5	8.50V	9.0	315	1226	4250	3875	830	830	158/155 K
12.00R24	20	8.5	8.50V	9.0	315	1226	4500	4125	900	900	160/157 K

### DRB892

#### All steel radial tire >>>

- Suitable for all wheels on common and higher level highway
- Good performance of tearing resistance and less uneven wear of tire shoulder
- Excellent in heat dispersion, for safe and comfortable driving



Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
7.50R20	14	6.0	6.5	6.50T	215	935	1900	1800	830	830	130/128 L
9.00R20	16	7.0	7.00T	7.5	259	1019	2800	2650	900	900	144/142 K
10.00R20	18	7.5	7.50V	8.0	278	1054	3250	3000	930	930	149/146 K
11.00R20	18	8.0	8.00V	8.5	293	1085	3550	3250	930	930	152/149 K
12.00R20	18	8.5	8.50V	9.0	315	1125	3750	3450	830	830	154/151 K
12.00R20	20	8.5	8.50V	9.0	315	1125	4000	3650	900	900	156/153 K
11R22.5	16	8.25	7.50		279	1054	3000	2725	830	830	146/143 L
12R22.5	18	9.00	8.25		300	1085	3550	3250	930	930	152/149 L
315/80R22.5	18	9.00	9.75		312	1076	3750	3450	830	830	154/151 L
315/80R22.5	20	9.00	9.75		312	1076	4125	3750	900	900	157/154 L



### DRB562



#### All steel radial tire >>>

- Suitable for driving wheels of dumping trucks in construction sites
- Strong traction and holding performance
- Excellent in tearing resistance, puncture and strong bearing capacity

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
9.00R20	16	7.0	7.00T	7.5	259	1030	2800	2650	900	900	144/142 J
10.00R20	18	7.5	7.50V	8.0	278	1065	3250	3000	930	930	149/146 J
11.00R20	18	8.0	8.00V	8.5	293	1096	3550	3250	930	930	152/149 J
12.00R20	18	8.5	8.50V	9.0	315	1136	3750	3450	830	830	154/151 J
12.00R20	20	8.5	8.50V	9.0	315	1136	4000	3650	900	900	156/153 J

### DRB592



#### All steel radial tire >>>

- Suitable for driving wheels in medium and long distance driving
- On common and higher grade road
- Excellent traction and draining performance
- Outstanding in anti-wear and high speed driving
- A higher original mileage

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
10.00R20	18	7.5	7.50V	8.0	278	1065	3250	3000	930	930	149/146 L
11.00R20	18	8.0	8.00V	8.5	293	1096	3550	3250	930	930	152/149 L
12.00R20	18	8.5	8.50V	9.0	315	1136	3750	3450	830	830	154/151 L
12.00R20	20	8.5	8.50V	9.0	315	1136	4000	3650	900	900	156/153 K
11R22.5	16	8.25		7.50	279	1065	3000	2725	830	830	146/143 M
12R22.5	18	9.00		8.25	300	1096	3550	3250	930	930	152/149 M
295/80R22.5	18	9.00		8.25	298	1068	3550	3250	900	900	152/149 M
315/80R22.5	18	9.00		9.75	312	1082	3750	3450	830	830	154/151 M
315/80R22.5	20	9.00		9.75	312	1082	4125	3750	900	900	157/154 M

### DRB662



#### All steel radial tire >>>

- Suitable for all wheels in medium and short distance driving
- On common and higher grade road
- Outstanding performance in anti-side-skid
- Noise avoidance and low rolling resistance
- Excellent in high speed driving and heat dispersion

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
11R22.5	16	8.25		7.50	279	1054	3000	2725	830	830	146/143 M
11R24.5	14	8.25		7.50	270	1099	3000	2725	720	720	146/143 M
11R24.5	16	8.25		7.50	270	1099	3250	3000	830	830	149/146 M
12R22.5	18	9.00		8.25	300	1085	3550	3250	930	930	152/149 M
295/75R22.5	14	9.00		8.25	294	1011	2800	2575	760	760	144/141 M
295/75R22.5	16	9.00		8.25	294	1011	3000	2725	830	830	146/143 M
295/80R22.5	18	9.00		8.25	298	1044	3550	3250	900	900	152/149 M
315/80R22.5	18	9.00		9.75	312	1076	3750	3450	830	830	154/151 M
315/80R22.5	20	9.00		9.75	312	1076	4125	3750	900	900	157/154 M

### DRB582



#### All steel radial tire >>>

- Suitable for all wheels on common and higher grade highway
- Excellent in anti-wet and skid performance as well as ground grasping
- Designed for different kinds of road condition
- Special tread formula and deeper tread depth provide a higher original mileage

Size	Ply Rating	Standard Rim	Allowed Rim	Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
						Single	Dual	Single	Dual	
11R22.5	16	8.25	7.50	279	1065	3000	2725	830	830	146/143 M
11R24.5	14	8.25	7.50	270	1112	3000	2725	720	720	146/143 M
11R24.5	16	8.25	7.50	270	1112	3250	3000	830	830	149/146 M
12R22.5	18	9.00	8.25	300	1096	3550	3250	930	930	152/149 M
295/75R22.5	14	9.00	8.25	294	1024	2800	2575	760	760	144/141 M
295/75R22.5	16	9.00	8.25	294	1024	3000	2725	830	830	146/143 M
295/80R22.5	18	9.00	8.25	291	1053	3550	3250	900	900	152/149 M
315/80R22.5	18	9.00	9.75	312	1082	3750	3450	830	830	154/151 M
315/80R22.5	20	9.00	9.75	312	1082	4125	3750	900	900	157/154 L

### DRB552



#### All steel radial tire >>>

- Suitable for driving wheels in medium and short distance driving
- On common and higher level road
- Excellent traction and water evacuation performance
- Outstanding in heat dispersion and high speed driving

Size	Ply Rating	Standard Rim	Allowed Rim	Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
						Single	Dual	Single	Dual	
11R22.5	16	8.25	7.50	279	1065	3000	2725	830	830	146/143 M
12R22.5	18	9.00	8.25	300	1096	3550	3250	930	930	152/149 M
295/75R22.5	14	9.00	8.25	294	1024	2800	2575	760	760	144/141 M
295/75R22.5	16	9.00	8.25	294	1024	3000	2725	830	830	146/143 M
315/80R22.5	18	9.00	9.75	312	1082	3750	3450	830	830	154/151 M
315/80R22.5	20	9.00	9.75	312	1082	4125	3750	900	900	157/154 L

### DRB695



#### All steel radial tire >>>

- Suitable for long distance transport of steer wheels and also trailer wheels
- On express way and quality road for high speed driving
- Outstanding in anti-side-skid, stability and low resistance of rolling
- Low heat and excellent in high speed performance

Size	Ply Rating	Standard Rim	Allowed Rim	Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
						Single	Dual	Single	Dual	
11R22.5	16	8.25	7.50	279	1065	3000	2725	830	830	146/143 M
12R22.5	18	9.00	8.25	300	1096	3550	3250	930	930	152/149 M
295/80R22.5	18	9.00	8.25	291	1043	3550	3250	900	900	152/149 M
315/80R22.5	18	9.00	9.75	312	1082	3750	3450	830	830	154/151 M
315/80R22.5	20	9.00	9.75	312	1082	4125	3750	900	900	157/154 L



### DRB595



#### All steel radial tire >>>

- Suitable for all wheels on express way and ordinary road for long distance transport
- Excellent anti-side-skid and water evacuation performance
- Outstanding in traction and wear resistance

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
10.00R20	18	7.5	7.50V	8.0	278	1065	3250	3000	930	930	149/146 K
11.00R20	18	8.0	8.00V	8.5	293	1096	3550	3250	930	930	152/149 K
12.00R20	18	8.5	8.50V	9.0	315	1136	3750	3450	830	830	154/141 K
12.00R20	20	8.5	8.50V	9.0	315	1136	4000	3650	900	900	156/153 K

### DRB566



#### All steel radial tire >>>

- Suitable for driving wheels of dumping trucks in short distance transport
- Lateral pattern with big blocks provide strong traction and ground grip performance
- Perform well in tough road condition such as mining area
- Excellent in tearing resistance and puncture proof, strong load carrying capacity

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
7.50R16LT	14	6.00G	5.50F	6.50H	215	815	1500	1320	770	770	122/118 J
8.25R16LT	16	6.50H	6.00G	6.5	235	865	1800	1600	770	770	128/124 J
8.25R20	16	6.5	6.50T	7.0 7.00T	236	974	2430	2300	930	930	139/137 J
9.00R20	16	7.0	7.00T	7.5	259	1030	2800	2650	900	900	144/142 J
10.00R20	18	7.5	7.50V	8.0	278	1065	3250	3000	930	930	149/146 J
11.00R20	18	8.0	8.00V	8.5	293	1096	3550	3250	930	930	152/149 J
12.00R20	18	8.5	8.50V	9.0	315	1136	3750	3450	830	830	154/151 J
12.00R20	20	8.5	8.50V	9.0	315	1136	4000	3650	900	900	156/153 J

### DRB568



#### All steel radial tire >>>

- Suitable for driving wheels on mixed and difficult road condition
- Excellent ground grip performance and road passing capability
- Outstanding in wear resistance, original mileage and heat dispersion

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
7.00R16LT	14	5.50F	6.00G		200	783	1320	1118	770	770	118/114 L
7.50R16LT	14	6.00G	5.50F	6.50H	215	815	1500	1320	770	770	122/118 L
8.25R16LT	16	6.50H	6.00G	6.5	235	865	1800	1600	770	770	128/124 L
12.00R24	18	8.5	8.50V	9.0	315	1226	4250	3875	830	830	158/155 K
12.00R24	20	8.5	8.50V	9.0	315	1238	4500	4125	900	900	160/157 K

### DRB588



#### All steel radial tire >>>

- Suitable for all wheels on mixed or even poor road condition
- Excellent in traction and ground grip performance
- High-performance tread formula provides outstanding wearing resistance

Size	Ply Rating	Standard Rim	Allowed Rim			Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
			6.50T	7.0	7.00T			Single	Dual	Single	Dual	
8.25R20	16	6.5	6.50T	7.0	7.00T	236	974	2430	2300	930	930	139/137 K
9.00R20	16	7.0	7.00T	7.5		259	1019	2800	2650	900	900	144/142 K
10.00R20	18	7.5	7.50V	8.0		278	1054	3250	3000	930	930	149/146 K
11.00R20	18	8.0	8.00V	8.5		293	1087	3550	3250	930	930	152/149 K
12.00R20	18	8.5	8.50V	9.0		315	1124	3750	3450	830	830	154/151 K
12.00R20	20	8.5	8.50V	9.0		315	1124	4000	3650	900	900	156/153 K

### DRB665



#### All steel radial tire >>>

- Suitable for trailer and steer wheels in medium and short distance driving
- On common and higher level road
- Outstanding in anti-side-skid and anti-irregular wear performance
- More stable, comfortable and safe driving

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
			12.25	12.25			Single	Dual	Single	Dual	
385/65R22.5	18	11.75	12.25	12.25	389	1072	4250		830		158 L
385/65R22.5	20	11.75	12.25	12.25	389	1072	4500		900		160 K

### DRB667



#### All steel radial tire >>>

- Suitable for trailer and steer wheels in medium and long distance driving
- On common and higher level road
- Outstanding in anti-side-skid and anti-irregular wear performance
- More stable, wear resistance loading capacity, and safe driving

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
			12.25	12.25			Single	Dual	Single	Dual	
385/65R22.5	18	11.75	12.25	12.25	389	1065	4250		830		158 L
385/65R22.5	20	11.75	12.25	12.25	389	1065	4500		900		160 K



### DRB599



#### All steel radial tire >>>

- Suitable for short distance transportation in mining area
- Ladder-design groove and anti-stone design deep in to the groove for better performance of anti-stone and anti-puncture
- Special tread compound formula provides excellent wearing resistance and puncture resistance
- Special design with big blocks and deep grooves provide excellent driving and traction performance
- Open-shoulder design enhances heat, soil dispersion and sewage disposal capacity

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
8.25R16LT	16	6.50H	6.00G	6.5	235	865	1800	1600	770	770	128/124 J
10.00R20	18	7.5	7.50V	8.0	278	1065	3250	3000	930	930	149/146 J
11.00R20	18	8.0	8.00V	8.5	293	1096	3550	3250	930	930	152/149 F
12.00R20	18	8.5	8.50V	9.0	315	1136	3750	3450	830	830	154/151 J
12.00R20	20	8.5	8.50V	9.0	315	1136	4000	3650	900	900	156/153 J

### DRB686



#### All steel radial tire >>>

- Suitable for steer wheels in long distance and high speed transportation
- Excellent in wear resistance, less fuel consumption for energy saving and environmental protection
- Special tread design provides outstanding handling and anti-side slip performance

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
12R22.5	18	9.00		8.25	300	1085	3550	3250	930	930	152/149 L

### DRB688



#### All steel radial tire >>>

- Suitable for trailer wheels in long distance and high speed transportation
- Excellent in wear resistance, less fuel consumption for energy saving and environmental protection
- Special groove design for irregular wearing resistance

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
							Single	Dual	Single	Dual	
12R22.5	18	9.00		8.25	300	1085	3550	3250	930	930	152/149 L

## DRB882



### All steel radial tire >>>

- Provides outstanding wet performance
- Provides outstanding wet performance
- Provides outstanding resistance to abrasion
- Provides excellent heat dissipation

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
			8.0	8.5			Single	Dual	Single	Dual	
11.00R20	18	8.0	8.0	8.5	293	1085	3550	3250	930	930	152/149 K

## DRB682



### All steel radial tire >>>

- Superior in wearing resistance and anti-irregular wear performance
- Deliver stone-ejecting property
- Anti-pinch stone, good anti-impact resistance
- Provides outstanding resistance to irregular abrasion

Size	Ply Rating	Standard Rim	Allowed Rim		Section Width (mm)	Diameter (mm)	Max Load (kg)		Pressure (kpa)		Load Index/Speed Rate
			8.0	8.5			Single	Dual	Single	Dual	
11.00R20	18	8.0	8.0	8.5	293	1085	3550	3250	930	930	152/149 K